



Lye application  
machine  
**Allround Peelboard**

The fastest lye application machine in its class!  
- now with peelboard feeding!



## BENEFIT

- equal showering results also on high speed because of 2 lye waterfall curtains plus patented WP Riehle lye shower
- the adjustable tankheater avoids the drop down of the lye temperature and guarantees constant shine and colour throughout the entire production time
- computer control for adjustable speed
- speedy control enables new feeding while the previous feed is still on the way
- long shower belt enables showering of large products
- tray deposit belt keeps baking trays clear from excess toppings
- rollable 47 gal lye tank
- tank lyelevel sensor prevents pump of running dry

## OPTIONS

- automatic scattering unit with brush roller, speed adjustable for different scattering toppings
- exchange toppings container for scattering unit

### TECHNISCHE DETAILS

### Tray size 18 x 26"

Length operational	158.0"
Length rest position	127.0"
Width	39.0"
Capacity	up to 400 trays/h
Weight	approx. 793 lb
Voltage 3-ph	208-240 V/60 Hz
max. connected load 208-240 V	9-10 kW
Lye tank capacity	approx. 47.5 gal

### WP LEBENSMITTELTECHNIK RIEHLE GMBH

Heinrich-Rieger-Str. 5 // D-73430 Aalen, Germany // Phone +49 7361 5580-0 // Fax +49 7361 5580-2281  
info@riehle.de // www.wp-riehle.de