



Enables a continuous frying process and constant frying results. The transfer conveyor with submerging belt transports the products automatically through the fryer and out at the other end. The submerged process shortens the frying time by up to 40%. The machine can be used with oil and also used with, for example, water, soup, broth, sauces and marinades



## **BENEFIT**

- Glass display control with 7 programs
- Digital heating control leads to a constant temperature and thus reduces fat absorption
- Reduction of working and frying time of up to 40% by submerged, continuous frying
- Constant frying results
- Easy cleaning by removing the transport unit and heating unit without tools
- Ideal for schnitzel, french fries, hamburger, chicken nuggets, fish and much more.

## **OPTIONS**

- Oil filter
- Automatic dosing devices
- Various infeed and transport belts available
- Increased heating power for extreme applications
- Customized feeding and discharging solutions
- Customized special equipment
- In different frying lengths and widths available
- With and without infeed belt available
- Extensive accessories available

TECHNICAL DETAILS	DLA 300 SC-1	DLA 300 SC-2	DLA 300 SC-3
Length	2,264 mm	3,200 mm	3,940 mm
Width	670 mm	670 mm	670 mm
Height	877 mm	877 mm	877 mm
Weight - empty	approx. 64 kg	арргох. 110 kg	арргох. 145 kg
Voltage	230 V/400 V-50 Hz	230 V/400 V-50 Hz	230 V/400 V-50 Hz
max. connected load	9.5 kW	18.5 kW	27.5 kW
Filling quantity	max. 50 ltr.	max. 95 ltr.	max. 150 ltr.
Usable width	284 mm	284 mm	284 mm
Frying distance in the oil	650 mm	1,370 mm	2,180 mm
Frying time	24 sec 6 min	1:12 sec 9 min	1:30 min 12 min
Product thickness	max. 5.5 cm	max. 5.5 cm	max. 5.5 cm

## WP LEBENSMITTELTECHNIK RIEHLE GMBH

Heinrich-Rieger-Str. 5 // D-73430 Aalen, Germany // Tel. +49 7361 5580-0 // Fax +49 7361 5580-2281 info@riehle.de // www.wp-riehle.de