









LYE APPLICATOR FOR ALL LYE BAKED GOODS IN HIGHEST QUALITY

TECHNICAL DATA



The integrated caustic lye tank ensures safe production with minimum space requirements

BENEFITS

- Intensive and constant showering result due to two lye waterfall curtains PLUS patented WP Riehle lye shower
- The adjustable heating prevents the lye temperature from dropping and ensures continuous shine and colour through the entire production time
- Computer control for adjustable production speed
- Easy to clean, motor and pump are maintenance-free
- Removable tables at the entrance and exit of the machine

OPTIONEN

- Scattering unit with brush roller, adjustable for different types of toppings
- Fermentation cloth, V-shape
- Fermentation cloth (with division)
- Aräometer for measurement of lye concentration

Tray size		580 x 780 mm	580 x 980 mm	
Length		2,100 mm	2,500 mm	
Length (closed)		1,500 mm	1,750 mm	
Height with salter		1,385 mm		
Height without salter		1,270 mm		
Width		795 mm		
Weight (empty)		approx. 180 kg	approx. 185 kg	
Voltage	3-ph	3x230 V/400	3x230 V/400 V/N/PE/50 Hz	
Max. connection load		5.1 kW/7.5 A		
Lye Shower		yes		
Lye curtains, additional		2		
Lye tank capacity		100 litres		
Lye tank heater		yes		
Lye Level indicator		yes		
Salter preparation		yes		
Salter		optional		
Tilting device		yes		
Computer control unit		yes		
Maintenance indicator		yes		



WP Lebensmitteltechnik RIEHLE GmbH Dr.-Rudolf-Schieber-Str. 15 D-73463 Westhausen | Germany phone: +49 7363 95390-0 info@riehle.de | www.wp-riehle.de